

AMENDMENTS
In the Claims

Current Status of Claims

- 1.(canceled)
- 2.(canceled)
- 3.(canceled)
- 4.(canceled)
- 5.(canceled)
- 6.(canceled)
- 7.(canceled)
- 8.(canceled)
- 9.(canceled)
- 10.(canceled)
- 11.(canceled)
- 12.(canceled)
- 13.(canceled)
- 14.(canceled)
- 15.(canceled)
- 16.(canceled)
- 17.(canceled)
- 18.(canceled)
- 19.(canceled)
- 20.(canceled)
- 21.(canceled)
- 22.(canceled)
- 23.(canceled)
- 24.(canceled)
- 25.(canceled)
- 26.(canceled)
- 27.(canceled)
- 28.(canceled)
- 29.(canceled)
- 30.(canceled)
- 31.(canceled)
- 32.(canceled)
- 33.(canceled)
- 34.(canceled)
- 35.(canceled)
- 36.(canceled)
- 37.(canceled)
- 38.(canceled)
- 39.(canceled)
- 40.(canceled)
- 41.(canceled)
- 42.(canceled)

43.(canceled)
44.(canceled)
45.(canceled)
46.(canceled)
47.(canceled)
48.(canceled)
49.(canceled)
50.(canceled)
51.(canceled)
52.(canceled)
53.(canceled)
54.(canceled)
55.(canceled)
56.(canceled)
57.(canceled)
58.(canceled)
59.(canceled)
60.(canceled)
61.(canceled)
62.(canceled)
63.(canceled)
64.(canceled)
65.(canceled)
66.(canceled)
67.(canceled)
68.(canceled)
69.(canceled)
70.(canceled)
71.(canceled)
72.(canceled)
73.(canceled)
74.(canceled)
75.(canceled)
76.(canceled)
77.(canceled)
78.(canceled)
79.(canceled)
80.(canceled)
81.(canceled)
82.(canceled)
83.(canceled)
84.(canceled)
84.(canceled)
85.(canceled)
86.(canceled)

87.(canceled)
88.(canceled)
89.(canceled)
90.(canceled)
91.(canceled)
92.(canceled)
93.(canceled)
94.(canceled)
95.(canceled)
96.(canceled)
97.(canceled)
98.(canceled)
99.(canceled)
100.(canceled)
101.(canceled)
102.(canceled)
103.(canceled)
104.(canceled)
105.(canceled)
106.(canceled)
107.(canceled)
108.(canceled)
109.(canceled)
110.(canceled)
111.(canceled)
112.(canceled)
113.(canceled)
114.(canceled)
115.(canceled)
116.(canceled)
117.(canceled)
118.(canceled)
119.(canceled)
120.(canceled)
121.(canceled)
122.(canceled)

1 123.(currently amended) A cross-laminate comprising:
2 a first coextruded film A having a main direction of uniaxial or unbalanced biaxial molecular
3 orientation and including:
4 a continuous main layer comprising a first polymer material selected to have a high
5 tensile strength,
6 a continuous bonding layer comprising a second polymer material and disposed on
7 a surface of the main layer, and
8 a plurality of substantially parallel film A first strands coextruded on a top surface
9 of the bonding layer in a spaced apart configuration, and comprising a third polymer
10 material different from the first and second polymer materials and comprising a
11 polymer consisting essentially of a copolymer of ethylene having a melting point or
12 a melting range within the temperature range of 50 - 100°C or a blend of such
13 copolymer and LLDPE containing at least 25% of the copolymer, where a separation
14 between adjacent film A first strands is no more than 8 cm measured from a middle
15 of one strand to a middle of an adjacent strand,
16 a second coextruded film B having a main direction of uniaxial or unbalanced biaxial
17 molecular orientation and including:
18 a continuous main layer comprising a fourth polymer material selected to have a high
19 tensile strength,
20 a continuous bonding layer comprising a fifth polymer material and disposed on a
21 surface of the main layer, and
22 a plurality of substantially parallel film B first strands coextruded on a top surface
23 of the bonding layer in a spaced apart configuration, and comprising a sixth polymer
24 material different from the fourth and fifth polymer materials, where a separation
25 between adjacent film B first strands is no more than 8 cm measured from a middle
26 of one strand to a middle of an adjacent strand,
27 where the film A and the film B are arranged such that their bonding layers and strands face
28 each other and such that the film B main direction crosses the film A main direction and the
29 film B first strands cross the film A first strands,
30 first bonds comprising points of intersection between the film A first strands and the film B
31 first strands,

second bonds comprising contact lines between the film A bonding layer and the film B first strands or the film B bonding layer and the film A first strands, and

third bonds comprising contact regions between the film A bonding layer and the film B bonding layer, where the regions are devoid of the film A first strands and the film B first strands, where the first bonds have a higher bond strength than a bond strength of the third bonds, where the strands have a thickness of no more than 30% of a thickness of their respective films at their thickest, and

where the strands comprise coextruded thin lines.

124.**(previously presented)** The cross-laminate according to claim 123, further comprising:

an exterior layer formed on an exterior surface of at least the film B comprising an exterior layer polymer material adapted to enhance a surface property of the laminate, where the property is selected from the group consisting of its heat-sealing capability and its frictional property.

125.**(previously presented)** The cross-laminate according to claim 123, wherein the second bonds have a bond strength greater than the bond strength of the third bonds.

126.**(currently amended)** The cross-laminate according to claim 123, wherein the first bonds comprise direct strand to strand lamination at the points of intersection between the film A first strands and the film B first strands.

127.**(previously presented)** The cross-laminate according to claim 123, further comprising:

a continuous extrusion lamination layer introduced between the films A and B, and wherein the first, second and third bonds further comprise portions of the continuous extrusion lamination layer.

128.**(currently amended)** The cross-laminate according to claim 123, wherein a collective area of the film A first strands and the film B first strands comprises no more than 60% of a surface area of their respective film sides.

129.**(previously presented)** The cross-laminate according to claim 123, wherein a thickness

1 increase of the films A and B at their respective strand locations is at most 20% of a film thickness
2 of the films A and B in adjacent regions of the films A and B devoid of their respective strands.

1 130.(previously presented) The cross-laminate according to claim 123, wherein a thickness
2 increase of the films A and B at their respective strand locations is at most 10% of a film thickness
3 of the films A and B in adjacent regions of the films A and B devoid of their respective strands.

1 131.(previously presented) The cross-laminate according to claim 123, wherein a volume of the
2 film A strands and the film B strands is not greater than 15% of a volume of their respective films.

1 132.(previously presented) The cross-laminate according to claim 123, wherein a volume of the
2 film A strands and the film B strands is not greater than 10% of a volume of their respective films.

1 133.(previously presented) The cross-laminate according to claim 123, wherein a volume of the
2 film A strands and the film B strands is not greater than 5% of a volume of their respective films.

1 134.(currently amended) The cross-laminate according to claim 123, wherein the separation
2 between first strands on films A and B is between 2 mm and 40 mm measured from a middle of one
3 strand to a middle of an adjacent strand.

1 135.(currently amended) The cross-laminate according to claim 123, wherein the separation
2 between first strands on films A and B is at the highest 20 mm measured from a middle of one strand
3 to a middle of an adjacent strand.

1 136.(previously presented) The cross-laminate according to claim 123, wherein:
2 the bond strength of the first bonds is at least 40 g cm⁻¹, as measured by a peel test carried
3 out on narrow specimens of the cross-laminate at a velocity of about 1 mm sec⁻¹, and
4 the bond strength of the third bonds are less than or equal to 75% of the bond strength of the
5 first bonds, as measured by the peel test.

1 137.(previously presented) The cross-laminate according to claim 136, wherein the bond strength

1 of the third bonds are less than or equal to 50% of the bond strength of the first bonds, as measured
2 by the peel test.

1 138.(previously presented) The cross-laminate according to claim 123, wherein an average
2 melting point of the third polymer material and average melting point of the sixth polymer materials
3 are at least about 10°C lower than an average melting point of the first polymer material and an
4 average melting point of the fourth polymer material.

1 139.(previously presented) The cross-laminate according to claim 123, wherein an average
2 melting point of the third polymer material and average melting point of the sixth polymer materials
3 are at least about 15°C lower than an average melting point of the first polymer material and an
4 average melting point of the fourth polymer material.

1 140.(previously presented) The cross-laminate according to claim 123, wherein an average
2 melting point of the third polymer material and average melting point of the sixth polymer materials
3 are at least about 20°C lower than an average melting point of the first polymer material and an
4 average melting point of the fourth polymer material.

1 141.(previously presented) The cross-laminate according to claim 123, wherein the main layer of
2 each of the two films A and B consists essentially of polyethylene or polypropylene.

1 142.(currently amended) The cross-laminate according to claim 123, wherein:
2 the main layers are selected from the group consisting of HDPE, LLDPE or a blend of the
3 two, and
4 the bonding layers comprise LLDPE in admixture with 5 - 25% of a copolymer of ethylene
5 having a melting point or a melting range within the temperature range of 50 - 80 °C; and
6 ~~the first strands comprise a polymer consisting essentially of a copolymer of ethylene having~~
7 ~~a melting point or a melting range within the temperature range of 50 - 100 °C or a blend of such~~
8 ~~copolymer and LLDPE containing at least 25% of the copolymer.~~

1 143.(previously presented) The cross-laminate according to claim 123, wherein the bonding layers

1 include an adhesion modifying material adapted to establish a blocking of the contacting mutually
2 facing surfaces of the films A and B to each other in regions devoid the their strands.

1 144.**(currently amended)** The cross-laminate according to claim 123, wherein:
2 at least one of the films A and B further including a plurality of substantially parallel second
3 strands,
4 where the second strands comprise a polymer material differing in composition, color and/or
5 appearance from the the first strands and
6 where the first and second strands on the film A or film B are interspersed.

1 145.**(previously presented)** The cross-laminate according to claim 123, wherein the polymer
2 material of the strands of at least one of the films A and B includes a colored material that makes the
3 colored strands visible through at least one side of the cross-laminate.

1 146.**(previously presented)** The cross-laminate according to claim 145, wherein the cross-laminate
2 has a thickness at its thickest of about 0.3 mm, and:
3 wherein an exterior surface of the film A is corrugated to form a visible pattern of striations
4 extending in one direction,
5 where a spacing of the striations being at most about 3 mm,
6 the main layer and the bonding layer of the film A are substantially transparent to enable the
7 colored strands to be visible when the laminate is observed from one of the exterior surfaces of the
8 cross-laminate, and
9 a depth of the corrugations is sufficient to impart a three-dimensional effect to the cross-
10 laminate such that the strands appear to be spaced internally from the exterior surface of the film A
11 a distance substantially greater than an actual maximum thickness of the film A.

1 147.**(currently amended)** A cross-laminate according to claim 123, wherein the film A further
2 includes:
3 a second continuous bonding layer comprising an seventh polymer material and
4 disposed on a second surface of the main layer, and
5 a plurality of substantially parallel film A third strands coextruded on a top surface

of the second bonding layer in a spaced apart configuration and comprising an eighth polymer material different from the first polymer material and seventh polymer material, and

the cross-laminate further comprising:

a third film C having a main direction of uniaxial or unbalanced biaxial molecular orientation and including:

a continuous main layer comprising a ninth polymer material having a high tensile strength,

a continuous bonding layer comprising a tenth polymer material and disposed on a surface of the main layer, and

substantially parallel film C first strands disposed on a top surface of the bonding layer in a spaced apart configuration and comprising an eleventh polymer material different from the ninth and tenth polymer materials,

where the film A and the film C are arranged such that their bonding layers and strands face each other and such that the film C main direction crosses the film A main direction and the film C first strands cross the film A third strands,

fourth bonds comprising points of intersection between the film A third strands and the film C first strands,

fifth bonds comprising contact lines between the film A bonding layer and the film C first strands or the film C bonding layer and the film A third strands, and

sixth bonds comprising contact regions between the film A bonding layer and the film C bonding layer, where the regions are devoid of the film A third strands and the film C first strands,

where the fourth bonds have a higher bond strength than the sixth bonds.

148.**(previously presented)** The cross-laminate according to claim 147, further comprising:

an exterior layer formed on an exterior surface of at least the film B or the film C comprising a polymer material adapted to enhance a surface property of the laminate, where the property is selected from the group consisting of its heat-sealing capability and its frictional property.

149.**(new)** The cross-laminate according to claim 123, wherein the film A first strands and the film B first strands are arranged in arrays, where distances between adjacent arrays of strands

1 measured from arrays center are the same or different and are between about 8cm and about 3 mm.

1 150.(new) The cross-laminate according to claim 144, wherein the film A first strands, the film
2 A second strands, the film B first strands and the film B second strands are arranged in arrays, where
3 a distance between adjacent arrays of strands measured from arrays center are the same or different
4 and are between about 8cm and about 3 mm.

1 151.(new) The cross-laminate according to claim 147, wherein the film A first strands, the film
2 A third strands, the film B first strands and the film C first strands are arranged in arrays, where a
3 distance between adjacent arrays of strands measured from arrays center are the same or different
4 and are between about 8cm and about 3 mm.